

The Delphion
Integrated
View

Other Views:
INPADOC

Title: **JP2000327382A2: ADMIXTURE FOR CEMENT**

Country: **JP Japan**

Kind: **A2 Document Laid open to Public inspection**

Inventor(s): **HANADA MINAMI
AOKI KAZUSHI
NISHIYAMA NAOHIRO
KOBAYASHI TOSHIMITSU
MIHASHI HIROZO**

Applicant/Assignee:



**THREE BOND CO LTD
NISHIMATSU CONSTR CO LTD
MIHASHI HIROZO**

News, Profiles, Stocks and More about this company

Issued/Filed Dates: **Nov. 28, 2000 / May 19, 1999**

Application Number: **JP1999000138494**

IPC Class: **C04B 22/12; C04B 22/08; C04B 24/02; C04B 24/06;
C04B 24/08; C04B 24/24; C04B 103/20;**

ECLA Code: **C04B20/10B; C04B40/06K;**

Priority Number(s): **May 19, 1999 JP1999000138494**


Abstract: **Problem to be solved:** To obtain an admixture that can maintain the fluidity for a long time, reduces the transportation trouble with reduced slump loss in the pumping and facilitates the cement casting into the framework by pulverizing an organic compound that is insoluble or slightly soluble in water in a specific temperature range and melts at a specific temperature in a specific average particle size and admixing a retardant to the powder.

Solution: The organic compound to be employed is insoluble or slightly soluble in water at 4-20°C, melts at 30-100°C and the average particle size is adjusted to 10-500 microns. In an embodiment, this organic compound is selected from the group consisting of wax, fat and oil, fatty acid, fatty acid ester, metallic soap, higher alcohol and thermoplastic resin. In a preferred embodiment, the retardant is selected from fluoride, phosphate, borate, hydroxycarboxylic acid (or its salt), ketocarboxylic acid (or its salt), saccharide or sugar alcohol. According to the slump flow test (JIS A 1101), the value is 18.0 cm, in the case of no addition of the retardant, while 13.0-14.0 cm in the case of 0.5 wt.% based on the cement.

COPYRIGHT: (C)2000, JPO

Family: Show known family members

Other Abstract Info: **CHEMABS 134(01)008307M CHEMABS 134(01)**



View
Image

1 page